

1/3" Format CS-mount Vari-focal Lenses

- 1/3" Format, CS-mount, Vari-focal Lenses
- Flexible Angular Field of View
- Three Different Lens Ranges Extending from 2.8mm up to 50mm
- Ideal for a Variety of Applications
- Manual Iris, DC Auto Iris, and Video Auto Iris
- Locking Mechanisms

SVCL-CS308xx
SVCL-CS2812xx
SVCL-CS550xx



SVCL-CS2812VA



SVCL-CS550VA



SVCL-CS550VM

SVCL-CS308xx
SVCL-CS2812xx
SVCL-CS550xx
1/3" FORMAT CS-MOUNT
VARI-FOCAL LENSES



SVCL-CS308VM



SVCL-CS308VA



SVCL-CS2812VM

Specifications

Model	SVCL-CS308VM	SVCL-CS308VA	SVCL-CS308VV	SVCL-CS2812VM	SVCL-2812VA	SVCL-CS550VM	SVCL-CS550VA
Focal Length	3.0-8mm	3.0-8mm	3.0-8mm	2.8-12mm	2.8-12mm	5-50mm	5-50mm
Imager Size	1/3"	1/3"	1/3"	1/3"	1/3"	1/3"	1/3"
Iris Type	Manual	DC	Video	Manual	DC	Manual	DC
Aperture Range	1.0-Close	1.0-360	1.4-360	1.0-Close	1.4-360	1.4-Close	1.4-185
Angle of View	91.0 x 66.6* 35.9 x 26.9**	91.0 x 66.6* 35.9 x 26.9**	91.0 x 66.6* 35.9 x 26.9**	97.4 x 72.5* 24.1 x 18.1**	97.4 x 72.5* 24.1 x 18.1**	53.6 x 40.2* 5.5 x 4.2**	53.6 x 40.2* 5.5 x 4.2**
Mount Type	CS-Mount	CS-Mount	CS-Mount	CS-Mount	CS-Mount	CS-Mount	CS-Mount
Operating Voltage	---	open:4.0V close:0.5V	---	---	open:4.0V close:0.5V	---	open:4.0V close:0.5V
MAX Voltage	---	6V	---	---	6V	---	6V
Power Supply	---	---	8.5~16V	---	---	---	---
Input Signal	---	---	VS or V Signal	---	---	---	---
Weight	~.11lbs (~48g)	~.16lbs (~72g)	~.165lbs (~75g)	~.16lbs (~72g)	~.17lbs (~79g)	~.18lbs (~84g)	~.21lbs (~95g)
Operating Temp.	-10°C~50°C	-10°C~50°C	-10°C~50°C	-10°C~50°C	-10°C~50°C	-10°C~60°C	-10°C~60°C

*(wide) **(tele)

