

Multi-Camera CCTV Power Supplies

- 4, 8, OR 16 Camera Power Supplies
- Self-restoring SmartFuses for Each Camera
- Entire Unit has a System Fuse
- Built-in Surge Suppression
- Large Metal Cabinet with Plenty of Space for Wiring
- Multiple Knockouts for Easy Installation
- On/Off Switch and LED Indicator
- Heavy Duty Version Available for Camera and Heater/Blower
- DC Version Available
- Comes with 6-foot Power Cord
- 3 Year Limited Warranty

VA - PS 2 4 4 0
VA - PS 2 4 8 0
VA - PS 2 4 1 6
VA - PS 2 4 1 6 HD
VA - PS 1 2 1 6 DC



VA-PS2440
VA-PS2480
VA-PS2416
VA-PS2416HD
VA-PS1216DC



Specifications

| Model | VA-PS2440 | VA-PS2480 | VA-PS2416 | VA-PS2416HD | VA-PS2416DC |
|--------------------|-----------------|-----------------|-----------------|-------------------------|-------------------------|
| Outputs | 4 | 8 | 16 | 16 | 16 |
| Max Amp/Ch | 1.85 | 1.85 | 1.85 | 3 | 1.1 |
| Total Amp/Unit | 4 | 4 | 8 | 16 | 5 |
| SmartFuse | Y | Y | Y | Y | Y |
| Surge Suppression | Y | Y | Y | Y | Y |
| Power Switch | Y | Y | Y | Y | Y |
| Input Voltage | 110V AC | 110V AC | 110V AC | 110V AC | 110V AC |
| Output Voltage | 24V AC | 24V AC | 24V AC | 24V AC | 9V - 15V DC |
| Surge Protection | 68V RMS, 8ns | 68V RMS, 8ns | 68V RMS, 8ns | 68V RMS, 8ns | 68V RMS, 8ns |
| Energy Rating | 0.7 Joules | 0.7 Joules | 0.7 Joules | 0.7 Joules | 0.7 Joules |
| Weight | 9 lbs | 9 lbs | 12 lbs | 16 lbs | 13 lbs |
| Dimensions (WxHxD) | 9 x 8 x 3.5 in. | 9 x 8 x 3.5 in. | 9 x 8 x 3.5 in. | 11.25 x 11.25 x 3.5 in. | 11.25 x 11.25 x 3.5 in. |
| LED | Y | Y | Y | Y | Y |
| DC | N | N | N | N | Y |

